



CONTENEURS DIMENSIONS

Dimensions intérieures	Ouverture portes	Volume	C.U.
20'DRY			
L : 5 898 mm I : 2 352 mm H : 2 393 mm	L : 2 340 mm H : 2 228 mm	33,2 cu.m	Max. GW : 30 480 kg Max. Payload : 28 250 kg Average Tare : 2 230 kg
40'DRY			
L : 12 032 mm I : 2 352 mm H : 2 393 mm	L : 2 340 mm H : 2 228 mm	67,8 cu.m	Max. GW : 30 480 kg Max. Payload : 26 740 kg Average Tare : 3 740 kg
40'HC			
L : 12 032 mm W : 2 352 mm H : 2 698 mm	L : 2 340 mm H : 2 585 mm	76,4 cu.m	Max. GW : 30 480 kg Max. Payload : 26 580 kg Average Tare : 3 900 kg
20'PALLETWIDE			
L : 5 898 mm I : 2 420 mm H : 2 382 mm	L : 2 360 mm H : 2 280 mm	34,1 cu.m	Max. GW : 30 480 kg Max. Payload : 28 005 kg Average Tare : 2 475 kg
40'PALLETWIDE			
L : 12 100 mm I : 2 420 mm H : 2 382 mm	L : 2 360 mm H : 2 280 mm	70 cu.m	Max. GW : 34 000 kg Max. Payload : 29 850 kg Average Tare : 4 150 kg
40'HC PALLETWIDE			
L : 12 100 mm I : 2 420 mm H : 2 698 mm	L : 2 360 mm H : 2 595 mm	79,1 cu.m	Max. GW : 34 000 kg Max. Payload : 29 850 kg Average Tare : 4 150 kg
20' REEFER			
L : 5 450 mm I : 2 288 mm	Cargo access height H : 2 221 mm	28,2 cu.m 27,3 cu.m under load line	Max. GW : 30 480 kg Max. Payload : 27 470 kg

H : 2 263 mm

Average Tare : 3 010 kg

40'HC REEFER

L : 11 584 mm

I : 2 288 mm

H : 2 545 mm

Cargo access height

H : 2 505 mm

67,5 cu.m
64,8 cu.m under load
line

Max. GW : 30 480/34 000 kg

Max. Payload : 25 800/29 130 kg

Average Tare : 4 680/4 870 kg

20' OPEN TOP

L : 5 895 mm

I : 2 350 mm

H : 2 346 mm

L : 2 342 mm

H : 2 279 mm

32 cu.m

Max. GW : 30 480 kg

Max. Payload : 28 230 kg

Average Tare : 2 250 kg

40' OPEN TOP

L : 12 028 mm

I : 2 350 mm

H : 2 346 mm

L : 2 342 mm

H : 2 279 mm

66 cu.m

Max. GW : 30 480 kg

Max. Payload : 26 780 kg

Average Tare : 3 700 kg

20' FLAT-RACK

Length between end walls : 5 920 mm

Side open length at floor : 5 558 mm

Width between posts : 2 227 mm

Height at posts : 2 233 mm

Max. GW : 34 000 kg

Max. Payload : 31 260 kg

Average Tare : 2 740 kg

40' FLAT-RACK

Length between end walls : 12 054 mm

Side open length at floor : 11 692 mm

Width between posts : 2 227 mm

Height at posts : 1 955 mm

Max. GW : 45 000 kg

Max. Payload : 40 050 kg

Average Tare : 4 950 kg

NB/Above mentioned data could vary as per factory and/or leasing co. specifications.